

TECHNO KRAFT ACRYLIC-BASED INSULATION

Elastomeric resin-based, UV-resistant
Waterproofing Material

PRODUCT DESCRIPTION

TECHNO KRAFT ACRYLIC-BASED INSULATION is a single-component, ready-to-use, high-elasticity, waterproof coating material.

FEATURES

- High UV resistance.
- Water vapour permeable.
- Easy to apply (roller & brush)
- Elastic.
- Resistant to standing water.
- Maintains flexibility at low temperatures.
- Adheres to metal surfaces.
- Creates a seamless waterproof coating.

APPLICATION AREAS

- Energy-efficient sloped roof insulation coatings
- Used as insulation material in both indoor and outdoor areas.
- Used for insulation of gutters, downspouts, chimney bases, and parapets.
- Can be used on horizontal and vertical surfaces as a coloured insulation material if desired.
- Sloped terrace roofs.
-

APPLICATION METHOD

Surface preparation:

Ensure that the surfaces to be coated are clean, dry, and sound. Dust, dirt, mould release agents, paint, and other coatings that may prevent adhesion must be removed from the surface. Weak surfaces, cracks, and surface defects must be repaired. If the surface to be applied is highly absorbent, it must be saturated with an appropriate primer. An anti-corrosive primer must be used for metal surfaces.

Application

TECHNO KRAFT ACRYLIC-BASED INSULATION should be mixed with a low-speed mixer for 2-3 minutes before use. The product can be diluted with water at a ratio of 30-40% as needed and used as a primer. Apply

KRAFTBAU CONSTRUCTION CHEMICALS MINING ENERGY GEOTHERMAL INDUSTRY AND TRADE INC.

HEADQUARTERS: Zübeyde Hanım Mah. Sarma Cad. 4/5 Altındağ/Ankara

Ankara Factory: ORHANIYE MAH. 2073. CAD. NO: 27-A KAHRAMANKAZAN/ANKARA

Antalya Factory: ÇIPLAKLI MAH. 2171. Cad. No:14 DÖŞEMEALTI/ANTALYA

E-MAIL: info@kraftbau.com.tr

TEL: 444 6 190

Kraftbau.com.tr

the primer-coated surface with a roller or brush until the entire surface is covered, applying a minimum of two coats horizontally and three coats vertically. The second coat should be applied after a minimum of 4 hours and a maximum of 24 hours after the first coat.

CONSUMPTION

1.50 – 1.80 kg/m²

PACKAGING

5 kg Packaging

20 kg Packaging

STORAGE / SHELF LIFE

- Protect from adverse weather conditions.
- Store in a dry, cool, closed environment (+10°C to +25°C).
- Once opened and mixed, the product should be consumed immediately.
- In unopened packaging, stored in dry places at a minimum temperature of +5 °C, it has a shelf life of 12 months.

TOOL CLEANING

Tools used can be cleaned with water; if the material is dry, it should be cleaned mechanically.

WARNINGS

- When applying in enclosed areas, ensure the area is well ventilated.
- In cold weather, packaging must be stored at a minimum temperature of +15°C for at least 24 hours prior to application.
- After application, the surface must be protected from water, rain, dew, snow, hail, frost, and similar environmental effects until it is completely dry.
- Use gloves, goggles, and protective clothing.
- If it comes into contact with skin, wash with soap and plenty of water.
- Do not swallow. Do not use empty containers for storing food or dispose of them in fire.
- For professional use only; store in a place inaccessible to children.

SAFETY

Users should refer to the latest Material Safety Data Sheets, which include physical, eco- logical, toxicological and other safety-related data, for information and advice on the safe transport, storage and disposal of chemical products.

KRAFTBAU CONSTRUCTION CHEMICALS MINING ENERGY GEOTHERMAL INDUSTRY AND TRADE INC.

HEADQUARTERS: Zübeyde Hanım Mah. Sarma Cad. 4/5 Altındağ/Ankara

Ankara Factory: ORHANIYE MAH. 2073. CAD. NO: 27-A KAHRAMANKAZAN/ANKARA

Antalya Factory: ÇIPLAKLI MAH. 2171. Cad. No:14 DÖŞEMEALTI/ANTALYA

E-MAIL: info@kraftbau.com.tr

TEL: 444 6 190

Kraftbau.com.tr

TECHNICAL SPECIFICATIONS

Colour	White, Grey, Terracotta Red, Green		
Density	1.35–1.45	kg/lit	+ 20°C, (EN ISO 2811-1)
Tensile Strength	>3.5	4	N/mm ²
Application Temperature	+5 °C	+35 °C	25°C / 55% RH
Initial drying time	6	8	hours
Coating acceptance time	4	24	hours
Application thickness	1	1.5	mm

LEGAL NOTICE

The information provided here regarding KRAFT POLYMER products, and in particular the recommendations for application and end use, is provided in good faith based on KRAFT POLYMER's current knowledge and experience under normal conditions and in accordance with KRAFT POLYMER's recommendations, provided that these products are stored, handled and applied correctly. Products, application surfaces, and application areas can vary significantly in practice. Therefore, when using KRAFT POLYMER products, ensure that you are using the correct product under the correct conditions and in the correct location, and strictly adhere to the information and instructions provided by KRAFT POLYMER regarding commercial suitability and/or suitability for a specific purpose. KRAFT POLYMER shall not be liable for any damages that may arise otherwise. The user of the product (user) must test the suitability of the product for the intended application and purpose. KRAFT POLYMER reserves the right to modify the properties of its products. The property rights of third parties must be respected. All orders are subject to our current terms and conditions regarding sales and shipping. Users must always refer to the latest version of the Product Information Sheet available from KRAFT POLYMER for the relevant product.

KRAFTBAU CONSTRUCTION CHEMICALS MINING ENERGY GEOTHERMAL INDUSTRY AND TRADE INC.

HEADQUARTERS: Zübeyde Hanım Mah. Sarma Cad. 4/5 Altındağ/Ankara

Ankara Factory: ORHANIYE MAH. 2073. CAD. NO: 27-A KAHRAMANKAZAN/ANKARA

Antalya Factory: ÇIPLAKLI MAH. 2171. Cad. No:14 DÖŞEMEALTI/ANTALYA

E-MAIL: info@kraftbau.com.tr

TEL: 444 6 190

Kraftbau.com.tr