



## Specifications

Working Height	66 ft	20.11 m
Platform Height	60 ft	18.47 m
Up and Over Height	26 ft 7 in	8.1 m
Platform Size	36 x 96 in	.91 x 2.44 m
Platform Capacity	500 lbs	227 Kg
Overall Width	8 ft	2.44 m
Stowed Length	26 ft 5 in	6.53 m
Stowed Height	8 ft 4 in	2.24 m
Jib Range of Articulation	144° (+78, -70) vertical	
Articulating Jib	6 ft	1.83 m
Ground Clearance (Axe)	12 in	30 cm
Tailswing	4ft	1.22 m
Outside Turning Radius	11 ft 8 in	3.56 m
Drive Speed	1 mph	1.6 km/h
Turret Rotation	360°	
Batteries	48v DC 750 Amp-Hr Battery	
Platform Rotation	180°	

\*Specifications Subject to Change

## Standard Equipment

- 60 ft Platform Height
- 66 ft Working Height
- 36 x 96 in Platform Size
- 12 in Ground Clearance
- Proportional Hydraulic Controls
- Platform Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm
- Movement Alarm
- 1/2' Airline to Platform



## Options

- Soft Touch System
- Fall Arrest System
- FMR System Fault Monitoring and Recording

\*May Change Capacity

## Safety

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Complaint