

Field of activity:

### Hazard to man and environment



#### Warning

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

### Preventive measures and rules of conduct



P102

Keep out of reach of children.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352

IF ON SKIN: Wash with plenty of water/soap.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



P308+P313

IF exposed or concerned: Get medical advice/attention.

P405

Store locked up.



Use acid resistant materials and devices.

Inspect electric installations more frequently for corrosion damage.

Provide good ventilation and/or an exhaust system in the work area. Dust should be exhausted directly at the point of origin.

Avoid generation of dust. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

Respiratory protection:

Respiratory protection must be worn whenever the WEL levels have been exceeded.

Dust mask or Combination filter Use combination filter type A-(P3) according to EN 14387.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Hand protection:

Protective gloves according to EN 374.

Glove material: Nitrile rubber-Layer thickness: 0.11 mm.

Breakthrough time: >480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection:

Tightly sealed goggles according to EN 166.

Body protection:

Wear suitable protective clothing.

Field of activity:

### Reaction in case of danger

Avoid generation of dust. Do not breathe dust.  
If possible, eliminate leakage. Provide adequate ventilation.  
Wear appropriate protective equipment. Keep unprotected people away.  
Take off contaminated clothing and wash it before reuse.

Extinguishing media:

Water spray jet, alcohol resistant foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

Accidental release measures:

Avoid generation of dust.

Collect dry and place in appropriate containers for disposal. Subsequent cleaning.

To clean the floor and all object contaminated by this material, use water. Use soda or another alkaline detergent for removal of residues.

### First aid

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin irritation, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth immediately and drink plenty of water. Seek medical attention.



### Appropriate disposal

Waste key number	20 01 14* Acids * = Evidence for disposal must be provided.
Product:	Special waste. Dispose of waste according to applicable legislation.
Contaminated packaging:	Waste key number 150101 - Paper and cardboard packaging Waste key number 150102 - Plastic packaging: OPP Dispose of waste according to applicable legislation. Non-contaminated packages may be recycled.