
## ELICA PRO SERIES TRENTO





Trento provides professional grade performance, while being discreetly mounted inside the cabinetry. It is available with a 600 CFM or 1200 CFM blower for extraordinary ventilating power. Plus the All-In-One design avoids the need to purchase a stainless liner. Hidden metallic in/out knob controls operate the 4-speed blower and LED lighting. A cleaner kitchen is ensured by Elica's patented angled baffle filters, which capture a higher percentage of contaminants and hold larger volumes of grease than traditional baffle filters.





	ETR628SS	ETR634SS ETR134S1	ETR146SS		
А	28 <sup>1</sup> ⁄2" (87.5 cm)	34 <sup>1</sup> ⁄2" (87.5 cm)	46 ½" (118.5 cm)		
В	18'' (45.7 cm)				
С	5 ⁄/۱۵" (13.8 cm)				
D	<sup>6</sup> ½" (16.4 cm)				
E	27%6" (70 cm)				
F	12716" (31.6 cm)				
G	29 <sup>13</sup> /16" (75.7 cm)				
Н	10 <sup>1</sup> /8" (25.7 cm)				
I	10" (25.4 cm)				
J	<sup>3</sup> ⁄4" (1.9 cm)				

## ELICA PRO SERIES TRENTO



## **SPECIFICATIONS**

Width:	28'' Unit	34" Unit	46" Unit			
Model:	ETR628SS	ETR634SS* ETR134S1**	ETR146SS			
Dimensions:	34 1/2"W x 18"D x 11 7/8"H	46 1/2"W x 18"D x 11 7/8"H				
Blower Type(internal):	600 CFM (4-speed)	600 CFM* / 1200 CFM**	1200 CFM (4-speed)			
Noise (sones):	7 Sones	7 Sones* 8.5 Sones**	8.5 Sones			
Finish: Controls:	Stainless Steel Fully retractable rotating knobs with blue backlighting					
Illumination:	2 LED, 6.5 W, 3000 K, 540 Lumen/Lamp					
Filter Type:	Dishwasher-Safe, Professional Stainless Steel Baffle					
Duct Transition:	2 for 34" & 3 for 46" 10" Round with BackDraft Damper (top only)					
Installation Type:	Ducted Installation Only					
Electrical:	120V - 60 Hz, 490 W	120V - 60 Hz, 490 W* 120V - 60 Hz, 913 W**	120V - 60 Hz, 926 W			
KITS:						
External Blower Kit:	KIT0153054 (1200 CFM)					
In-line Blower Kit:	KIT0154387 (1200 CFM)					
CFM Reduction KIT:	KIT0185752 (for 600 CFM Blower), KIT0185099 (for 1200 CFM Blower)					
10" to 8" transition KIT:	KIT0154387 (1200 CFM)					
WARRANTY:***	Two (2) Years Parts & In-Home Labor. Earn an additional One (1) Year of Parts & In-Home Labor by registering on elica.com.					

## PLUS FEATURES

HUSH SYSTEM - An exclusive sound deadening technology that effectivelyreduces sound levels by over 35%

SEAMLESS CRAFTSMANSHIP - Heavy gauge stainless steel "Seamless" construction that delivers refined elegance.

LED CONSUMER REPLACEABLE BULB - High quality LED lighting usually requires a skilled technician to replace lamps. Avoid this expense with Elica's new LED lamps that enable homeowners to replace in seconds STAINLESS STEEL BAFFLE FILTERS WITH GREASE COLLECTORS -Designed for high airflow cooking, the "S" shape design traps high volumes of grease



4

PROFESSIONAL PERFORMANCE - Special features and high performances for models with aspiration capacity between 600 and 1200 CFM's

HEAT GUARD - Senses extreme temperatures (>316 °F) and automatically adjusts the blower speed to HIGH



Model	HVI Certified Ratings	High Speed	Working Speed	Duct Size
ETR146SS	CFM	860	320	10" (Vertical)
ETR134S1	Sones	12.5	2	10" (Vertical)
ETR634SS	CFM	500	180	10" (Vertical)
ETR628SS	Sones	9.5	2	10" (Vertical)

\* The product images shown are for illustration purposes only and may not be an exact representation of the product.

\*\* Blower performance indicates the performance of the blower by itself. Performance claims are not HVI certified but were established in accordance with HVI Standardized test procedure. For Certified Ratings, please refer to HVI Certified Product Directory. Electric Ratings are declared according to UL.

 $^{\ast\ast\ast\ast}$  For valid warranty extension, register within 3 months from purchase. For USA & Canada Users Only.