



FLASH TEST REPORT

Execution

State of charge **41 %**
Date 10/08/2023 10:25:54
Executed by Carla AB

Vehicle

Brand Cupra
Model Born - 77 kWh
VIN VSSZZK1XPP008968
Mileage 12,633 km

Analysis Result

AVILOO SCORE

100
/ 100

High voltage battery usage and history

Analysis of charging & driving behavior

50 / 50

High voltage battery performance

Analysis of cell voltages and module temperatures.

30 / 30

High voltage battery control unit

Check of signals and calculations of the battery management control unit.

10 / 10

Electrical low voltage system

Check of 12 V battery state and power supply.

5 / 5

Vehicle communication interface

Check of communication via the diagnostic interface.

5 / 5

DI Wolfgang Berger MBA
Managing director

DI Nikolaus Mayerhofer
Managing director

Dr. Marcus Berger
COO/CFO and Partner



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

10:25:51	AVILOO Box connected.
10:25:54	Flash Test started.
10:25:57	Vehicle detected.
10:26:02	Starting data acquisition.
10:28:03	Finished data acquisition.
10:28:14	Analyzing data.
10:28:15	Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	VSSZZK1XPP008968
Date	10/08/2023 10:25:54
Mileage	12,633 km

Measurements High Voltage System

Battery temperature	18.25 °C
Maximum cell temperature deviation	0.38 °C
Pack voltage	350.06 V
Maximum cell voltage deviation	3.91 mV
Peak current during check	-2.18 A
State of Health (SoH - read from car manufacturer)*	101.82 %

Measurements Low Voltage System

Power supply 12V system	14.58 V
-------------------------	---------

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.

