



FLASH TEST REPORT

Execution

State of charge Date Executed by 21 % 23/01/2024 14:59:08 Carla AB

Vehicle

Brand Model VIN Mileage

Tesla Model Y - 78,8 kWh LRWYGCEK9NC256327 31,324 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	66 / 70
High voltage battery performance Analysis of cell voltages and module temperatures.	28 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	 ✓
Vehicle communication interface Check of communication via the diagnostic interface.	~

Dr. Marcus Berger CEO and Partner

DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

14.00.00 AVIEOO Dox connected.	14:59:05	AVILOO Box connected.
--------------------------------	----------	-----------------------

- ✓ FLASH Test started.
- ✓ Vehicle detected.
- Starting data acquisition.
- ✓ Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

Maaguramanta High Valtaga System			
Mileage	31,324 km		
Date	23/01/2024 14:59:08		
VIN	LRWYGCEK9NC256327		

Measurements High Voltage System

Battery temperature	15 °C
Maximum cell temperature deviation	0.5 °C
Pack voltage	341.41 V
Maximum cell voltage deviation	2 mV
Peak current during check	-11.76 A
State of Health (SoH - read from car manufacturer)*	94.54 %

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



AVILOO GmbH

Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

