



FLASH TEST REPORT

Execution

State of charge Date Executed by 84 % 17/11/2023 13:19:55 Carla AB

Vehicle

Brand Model VIN Mileage Tesla Model 3 - 77,8 kWh 5YJ3E7EC3LF779071 22,285 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	64 / 70
High voltage battery performance Analysis of cell voltages and module temperatures.	28 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	 ✓
Vehicle communication interface Check of communication via the diagnostic interface.	 ✓

DI Wolfgang Berger MBA Managing director



DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

- ✔ Flash Test started.
- ✓ Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN Date	5YJ3E7EC3LF779071 17/11/2023 13:19:55
Mileage	22,285 km
Measurements High Voltage System	
Battery temperature	16 5 °C

Battery temperature	16.5 °C
Maximum cell temperature deviation	1.5 °C
Pack voltage	390.77 V
Maximum cell voltage deviation	4 mV
Peak current during check	-7.07 A
State of Health (SoH - read from car manufacturer)*	95.27 %

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



AVILOO GmbH

Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

