



FLASH TEST REPORT

Execution

State of charge **2.18 %**
Date 11/10/2024 13:50:38
Executed by Carla AB

Vehicle

Brand Tesla
Model Model S
VIN 5YJSA7E27JF239055
Mileage 54,902 km

Analysis Result

AVILOO SCORE

93
/ 100

High voltage battery usage and history

Analysis of charging & driving behavior

65 / 70

High voltage battery performance

Analysis of cell voltages and module temperatures.

28 / 30

High voltage battery control unit

Check of signals and calculations of the battery management control unit.



Vehicle communication interface

Check of communication via the diagnostic interface.



Dr. Marcus Berger
CEO and Partner

DI Wolfgang Berger MBA
CSO and Founder

DI Nikolaus Mayerhofer
CTO and Founder



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

- 13:50:35 AVILOO Box connected.
- ✓ FLASH Test started.
- ✓ Starting data acquisition.
- ✓ Vehicle detected.
- ✓ Finished data acquisition.
- ✓ Analyzing data.
- ✓ Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	5YJSA7E27JF239055
Date	11/10/2024 13:50:38
Mileage	54,902 km

Measurements High Voltage System

Battery temperature	12.94 °C
Maximum cell temperature deviation	0.71 °C
Pack voltage	269.62 V
Maximum cell voltage deviation	31.68 mV
Peak current during check	-6.58 A

