



FLASH TEST REPORT

Execution

State of charge Date Executed by

Vehicle

62.5 % 16/08/2023 10:10:24 Carla AB Brand Model VIN Mileage

Volkswagen ID4 - 77 kWh WVGZZZE2ZNP056268 17,393 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	49 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	29 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	5 / 5
Vehicle communication interface Check of communication via the diagnostic interface.	5 / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

10:10:21 AVILOO Box connected.
10:10:24 Flash Test started.
10:10:28 Vehicle detected.
10:10:32 Starting data acquisition.
10:12:32 Finished data acquisition.
10:12:45 Analyzing data.
10:12:46 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN

Date
Mileage

Measurements High Voltage System

Battery temperature

Maximum cell temperature deviation

Pack voltage

Maximum cell voltage deviation

Maximum cell voltage deviation

16/08/2023 10:10:24

17,393 km

19.88 °C

0.75 °C

9ack voltage

365.25 V

6.84 mV

Measurements Low Voltage System

State of Health (SoH - read from car manufacturer)*

Peak current during check

Power supply 12V system 14.45 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h



-4.12 A

97.6 %

WVGZZZE2ZNP056268