



FLASH TEST REPORT

| Execution | Vehicle |
|-----------|---------|
| | |

State of charge 92.88 %
Date 22/08/2023 07:47:54
Executed by Carla AB

92.88 % Brand 08/2023 07:47:54 Model Carla AB VIN Mileage Renault Zoe VF1AG000762148657 44,907 km

Analysis Result

AVILOO SCORE



| High voltage battery usage and history Analysis of charging & driving behavior | 45 / 50 |
|---|----------------|
| High voltage battery performance Analysis of cell voltages and module temperatures. | 28 / 30 |
| High voltage battery control unit Check of signals and calculations of the battery management control unit. | 10 / 10 |
| Electrical low voltage system Check of 12 V battery state and power supply. | 5 / 5 |
| Vehicle communication interface Check of communication via the diagnostic interface. | 5 / 5 |

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

07:47:51 AVILOO Box connected.

07:47:54 Flash Test started.

07:47:59 Vehicle detected.

07:48:02 Starting data acquisition.

07:50:02 Finished data acquisition.

07:50:09 Analyzing data.

07:50:10 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 VF1AG000762148657

 Date
 22/08/2023 07:47:54

 Mileage
 44,907 km

Measurements High Voltage System

Battery temperature 23 °C

Maximum cell temperature deviation 2 °C

Pack voltage 389.11 V

Maximum cell voltage deviation 10 mV

Peak current during check -2.75 A

State of Health (SoH - read from car manufacturer)*

Measurements Low Voltage System

Power supply 12V system 13.42 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h

