



FLASH TEST REPORT

Execution

State of charge 92.4 %
Date 27/05/2025 10:32:02
Executed by Carla AB

Vehicle

Brand MG Automotive
Model Marvel R - 69,9 kWh
VIN LSJE24091NS090193
Mileage 57,153 km

Analysis Result

AVILOO SCORE

96
/ 100

High voltage battery usage and history
Analysis of charging & driving behavior

67 / 70

High voltage battery performance
Analysis of cell voltages and module temperatures.

29 / 30

High voltage battery control unit
Check of signals and calculations of the battery management control unit.



Vehicle communication interface
Check of communication via the diagnostic interface.



Dr. Marcus Berger
CEO and Partner

DI Wolfgang Berger MBA
CSO and Founder

DI Nikolaus Mayerhofer
CTO and Founder



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

- 10:31:58
- AVILOO Box connected.
- ✓
- FLASH Test started.
- ✓
- Vehicle detected.
- ✓
- Starting data acquisition.
- ✓
- Finished data acquisition.
- ✓
- Analyzing data.
- ✓
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

Date	27/05/2025 10:32:02
Mileage	57,153 km
VIN	LSJE24091NS090193

Measurements High Voltage System

Battery temperature	14 °C
Maximum cell temperature deviation	0.5 °C
Pack voltage	401.75 V
Maximum cell voltage deviation	16 mV
Peak current during check	-3.52 A
State of Health (SoH - read from car manufacturer)*	97.28 %

fastcheck.certificate.explanationFooterText

