



FLASH TEST REPORT

Execution

State of charge Date Executed by 18 % 18/11/2023 11:22:15 Carla AB

Vehicle

Brand Model VIN Mileage Nissan Leaf ZE1 SJNFAAZE1U0168652 20,425 km

Analysis Result

AVILOO SCORE

97 / 100	
	68 / 70

Analysis of charging & driving behavior	68 / 70
High voltage battery performance Analysis of cell voltages and module temperatures.	29 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	v
Vehicle communication interface Check of communication via the diagnostic interface.	v

DI Wolfgang Berger MBA Managing director

High voltage battery usage and history



DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

11:22:12 A	VILOO Box connected.
------------	----------------------

- ✓ Flash Test started.
- ✓ Vehicle detected.
- Starting data acquisition.
- ✓ Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

Measurements High Voltage System			
Mileage	20,425 km		
Date	18/11/2023 11:22:15		
VIN	SJNFAAZE1U0168652		

Battery temperature	0°C
Maximum cell temperature deviation	0°C
Pack voltage	343.69 V
Maximum cell voltage deviation	10.02 mV
Peak current during check	-12.52 A
State of Health (SoH - read from car manufacturer)*	96.1 %

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



AVILOO GmbH

Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

