



FLASH TEST REPORT

Execution

State of charge **61.45 %**
Date 05/10/2023 10:32:07
Executed by Carla AB

Vehicle

Brand Tesla
Model Model S
VIN 5YJSA7E2XHF187804
Mileage 88,729 km

Analysis Result

AVILOO SCORE

94
/ 100

High voltage battery usage and history
Analysis of charging & driving behavior

66 / 70

High voltage battery performance
Analysis of cell voltages and module temperatures.

28 / 30

High voltage battery control unit
Check of signals and calculations of the battery management control unit.




Vehicle communication interface
Check of communication via the diagnostic interface.




DI Wolfgang Berger MBA
Managing director


DI Nikolaus Mayerhofer
Managing director


Dr. Marcus Berger
COO/CFO and Partner



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

10:32:04 AVILOO Box connected.
✓ Flash Test started.
✓ Starting data acquisition.
✓ Vehicle detected.
✓ Finished data acquisition.
✓ Analyzing data.
✓ Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	5YJSA7E2XHF187804
Date	05/10/2023 10:32:07
Mileage	88,729 km

Measurements High Voltage System

Battery temperature	10.86 °C
Maximum cell temperature deviation	2.02 °C
Pack voltage	372.02 V
Maximum cell voltage deviation	5.76 mV
Peak current during check	-4.59 A

