



# **FLASH TEST REPORT**

## Execution

State of charge Date Executed by 21 % 26/01/2024 08:14:00 Carla AB

## Vehicle

Brand Model VIN Mileage Tesla Model Y - 78,8 kWh LRWYGCEK9NC241536 55,189 km

# **Analysis Result**

# **AVILOO SCORE**

<b>93</b> / 100	
<b>65</b> / 70	
28 ( 20	

Analysis of charging & driving behavior	65 / 70
High voltage battery performance Analysis of cell voltages and module temperatures.	<b>28</b> / 30
<b>High voltage battery control unit</b> Check of signals and calculations of the battery management control unit.	•

### **Vehicle communication interface** Check of communication via the diagnostic interface.

High voltage battery usage and history

Belge

Dr. Marcus Berger CEO and Partner

DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





## EXPLANATION OF THE BATTERY FLASH TEST

### **ANALYSIS METHOD**

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

## FLASH TEST EXECUTION PROTOCOL

08:13:57 AV	VILOO Box	connected.
-------------	-----------	------------

- ✔ FLASH Test started.
- Vehicle detected.
- Starting data acquisition.
- ✓ Finished data acquisition.
- Analyzing data.
- Analysis completed.

### DETAILED RESULTS OF PERFORMED CHECKS

#### **Vehicle Information**

VIN	LRWYGCEK9NC241536
Date	26/01/2024 08:14:00
Mileage	55,189 km

#### Measurements High Voltage System

Battery temperature	15 °C
Maximum cell temperature deviation	1.5 °C
Pack voltage	342.75 V
Maximum cell voltage deviation	6 mV
Peak current during check	-4.81 A
State of Health (SoH - read from car manufacturer)*	93.43 %

\*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



#### **AVILOO GmbH**

Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

