



FLASH TEST REPORT

Execution

State of charge **77 %**
Date 03/06/2025 09:31:44
Executed by Carla AB

Vehicle

Brand Audi
Model Q4 e-tron - 77 kWh
VIN WAUZZZFZ6PP071094
Mileage 59,618 km

Analysis Result

AVILOO SCORE

98
/ 100

High voltage battery usage and history
Analysis of charging & driving behavior

68 / 70

High voltage battery performance
Analysis of cell voltages and module temperatures.

30 / 30

High voltage battery control unit
Check of signals and calculations of the battery management control unit.



Vehicle communication interface
Check of communication via the diagnostic interface.



Dr. Marcus Berger
CEO and Partner

DI Wolfgang Berger MBA
CSO and Founder

DI Nikolaus Mayerhofer
CTO and Founder



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

- 09:31:41
- ✓ AVILOO Box connected.
 - ✓ FLASH Test started.
 - ✓ Vehicle detected.
 - ✓ Starting data acquisition.
 - ✓ Finished data acquisition.
 - ✓ Analyzing data.
 - ✓ Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

Date	03/06/2025 09:31:44
Mileage	59,618 km
VIN	WAUZZZFZ6PP071094

Measurements High Voltage System

Battery temperature	20.25 °C
Maximum cell temperature deviation	0.75 °C
Pack voltage	379 V
Maximum cell voltage deviation	4.89 mV
Peak current during check	-2.23 A
State of Health (SoH - read from car manufacturer)*	99.09 %

fastcheck.certificate.explanationFooterText

