



# FLASH TEST REPORT

## Execution

State of charge **43.32 %**  
Date 22/05/2025 14:27:50  
Executed by Carla AB

## Vehicle

Brand Tesla  
Model Model X  
VIN 5YJXCCE23MF318249  
Mileage 83,684 km

## Analysis Result

# AVILOO SCORE

**94**  
/ 100

**High voltage battery usage and history**  
Analysis of charging & driving behavior

**66** / 70

**High voltage battery performance**  
Analysis of cell voltages and module temperatures.

**28** / 30

**High voltage battery control unit**  
Check of signals and calculations of the battery management control unit.



**Vehicle communication interface**  
Check of communication via the diagnostic interface.



Dr. Marcus Berger  
CEO and Partner

DI Wolfgang Berger MBA  
CSO and Founder

DI Nikolaus Mayerhofer  
CTO and Founder



# EXPLANATION OF THE BATTERY FLASH TEST

## ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

## FLASH TEST EXECUTION PROTOCOL

- 14:27:46
- AVILOO Box connected.
  - ✓ FLASH Test started.
  - ✓ Starting data acquisition.
  - ✓ Vehicle detected.
  - ✓ Finished data acquisition.
  - ✓ Analyzing data.
  - ✓ Analysis completed.

## DETAILED RESULTS OF PERFORMED CHECKS

### Vehicle Information

Date	22/05/2025 14:27:50
Mileage	83,684 km
VIN	5YJXCCE23MF318249

### Measurements High Voltage System

Battery temperature	19.72 °C
Maximum cell temperature deviation	2.01 °C
Pack voltage	358.62 V
Maximum cell voltage deviation	10.71 mV
Peak current during check	-4.43 A

