



# **FLASH TEST REPORT**

31/08/2023 11:27:19

#### Execution

State of charge Date Executed by

### **Vehicle**

Brand Model VIN Mileage

19 %

Carla AB

Tesla Model 3 - 77,8 kWh 5YJ3E7EB3LF562949 94,298 km

### **Analysis Result**

# **AVILOO SCORE**



## High voltage battery usage and history

Analysis of charging & driving behavior

**62** / 70

#### High voltage battery performance

Analysis of cell voltages and module temperatures.

**27** / 30

#### High voltage battery control unit

Check of signals and calculations of the battery management control unit.



#### Vehicle communication interface

Check of communication via the diagnostic interface.



DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





# EXPLANATION OF THE BATTERY FLASH TEST

#### **ANALYSIS METHOD**

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

#### FLASH TEST EXECUTION PROTOCOL

11:27:16 AVILOO Box connected.

- Flash Test started.
- ✓ Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

#### **DETAILED RESULTS OF PERFORMED CHECKS**

#### **Vehicle Information**

 VIN
 5YJ3E7EB3LF562949

 Date
 31/08/2023 11:27:19

 Mileage
 94,298 km

#### Measurements High Voltage System

Battery temperature 17.5 °C

Maximum cell temperature deviation 1 °C

Pack voltage 335.29 V

Maximum cell voltage deviation 4 mV

Peak current during check -8.49 A

State of Health (SoH - read from car manufacturer)\* 89.49 %

\*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h

