



FLASH TEST REPORT

State of charge Date Executed by

44.21 % 21/08/2023 14:24:53 Carla AB Brand Model VIN Mileage

Vehicle

Renault Zoe VF1AG000363243906 49,933 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	43 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	27 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	5 / 5
Vehicle communication interface Check of communication via the diagnostic interface.	5 / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

14:24:50 AVILOO Box connected.
14:24:53 Flash Test started.
14:24:56 Vehicle detected.
14:25:01 Starting data acquisition.
14:27:01 Finished data acquisition.
14:27:07 Analyzing data.
14:27:08 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 VF1AG000363243906

 Date
 21/08/2023 14:24:53

 Mileage
 49,933 km

Measurements High Voltage System

Battery temperature 18 °C

Maximum cell temperature deviation 0 °C

Pack voltage 350.76 V

Maximum cell voltage deviation 5.9 mV

Peak current during check -3.17 A

State of Health (SoH - read from car manufacturer)*

Measurements Low Voltage System

Power supply 12V system 13.43 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h

