



# FLASH TEST REPORT

**Execution** Vehicle

State of charge 42.1 %
Date 07/02/2025 07:54:11
Executed by Carla AB

Carla AB VI

Model VIN Mileage

Brand

Peugeot 208e - 50 kWh VR3UHZKXZMT115256 43,638 km

**Analysis Result** 

# **AVILOO SCORE**



High voltage battery usage and history

Analysis of charging & driving behavior

**65** / 70

High voltage battery performance

Analysis of cell voltages and module temperatures.

**27** / 30

High voltage battery control unit

Check of signals and calculations of the battery management control unit.



Vehicle communication interface

Check of communication via the diagnostic interface.



Dr. Marcus Berger CEO and Partner DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





## **EXPLANATION OF THE BATTERY FLASH TEST**

#### **ANALYSIS METHOD**

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

#### FLASH TEST EXECUTION PROTOCOL

07:54:07 AVILOO Box connected.

- FLASH Test started.
- Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

#### **DETAILED RESULTS OF PERFORMED CHECKS**

#### **Vehicle Information**

VIN VR3UHZKXZMT115256 Date 07/02/2025 07:54:11 Mileage 43,638 km

### Measurements High Voltage System

17 °C Battery temperature Maximum cell temperature deviation 4°C 391.5 V Pack voltage Maximum cell voltage deviation 10.04 mV Peak current during check -23.85 A State of Health (SoH - read from car manufacturer)\* 91.38 %



Mail: info@aviloo.com UID Nr.: ATU 737 81605



<sup>\*</sup>The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.