

FLASH TEST REPORT

Execution

State of charge 0 %
Date 04/09/2023 09:12:40
Executed by Carla AB

Vehicle

Brand Tesla
Model Model X
VIN 5YJXCCE42MF311603
Mileage 69,328 km

Analysis Result

AVILOO SCORE

93
/ 100

High voltage battery usage and history
Analysis of charging & driving behavior

66 / 70

High voltage battery performance
Analysis of cell voltages and module temperatures.

27 / 30

High voltage battery control unit
Check of signals and calculations of the battery management control unit.




Vehicle communication interface
Check of communication via the diagnostic interface.




DI Wolfgang Berger MBA
Managing director


DI Nikolaus Mayerhofer
Managing director


Dr. Marcus Berger
COO/CFO and Partner



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

09:12:37 AVILOO Box connected.
✓ Flash Test started.
✓ Starting data acquisition.
✓ Vehicle detected.
✓ Finished data acquisition.
✓ Analyzing data.
✓ Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	5YJXCCE42MF311603
Date	04/09/2023 09:12:40
Mileage	69,328 km

Measurements High Voltage System

Battery temperature	21.39 °C
Maximum cell temperature deviation	1.62 °C
Pack voltage	301.56 V
Maximum cell voltage deviation	65.28 mV
Peak current during check	-5.85 A

