



FLASH TEST REPORT

Execution

State of charge 94.5 % 21/08/2024 15:54:53 Date

Executed by Carla AB

Vehicle

Brand Model VIN

Mileage

Audi e-tron 55 - 95 kWh WAUZZZGE7NB045237

44,673 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history

68 / 70 Analysis of charging & driving behavior

High voltage battery performance

29 / 30 Analysis of cell voltages and module temperatures.

High voltage battery control unit

Check of signals and calculations of the battery management control unit.

Vehicle communication interface

Check of communication via the diagnostic interface.

Dr. Marcus Berger CEO and Partner

DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

15:54:50 AVILOO Box connected.

- FLASH Test started.
- Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN WAUZZZGE7NB045237 Date 21/08/2024 15:54:53 Mileage 44,673 km

Measurements High Voltage System

21 °C Battery temperature Maximum cell temperature deviation 1°C 440.74 V Pack voltage Maximum cell voltage deviation 2 mV Peak current during check -4.05 A State of Health (SoH - read from car manufacturer)* 96 %



Web: www.aviloo.com FN: 502117 h

Mail: info@aviloo.com UID Nr.: ATU 737 81605



^{*}The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.