



FLASH TEST REPORT

Execution Vehicle

State of charge
Date 06/11/2024 1
Executed by C

06/11/2024 14:43:51 Carla AB

91 %

Brand Model VIN YSN Mileage

Polestar 2 - 78 kWh YSMVSEGE1PL124905 67,035 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history

Analysis of charging & driving behavior

Analysis of charging & driving behavior

High voltage battery performanceAnalysis of cell voltages and module temperatures.

High voltage battery control unit

Check of signals and calculations of the battery management control unit.

Vehicle communication interface

Check of communication via the diagnostic interface.

30 / 30

68 / 70

1

Dr. Marcus Berger CEO and Partner DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

14:43:48 AVILOO Box connected.

- FLASH Test started.
- 1 Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN YSMVSEGE1PL124905 Date 06/11/2024 14:43:51 Mileage 67,035 km

Measurements High Voltage System

10.4 °C Battery temperature Maximum cell temperature deviation 2.6 °C 450.2 V Pack voltage Maximum cell voltage deviation 12.85 mV Peak current during check -13.99 A State of Health (SoH - read from car manufacturer)* 97.54 %



Web: www.aviloo.com FN: 502117 h

Mail: info@aviloo.com UID Nr.: ATU 737 81605



^{*}The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.