



# FLASH TEST REPORT

## Execution

State of charge **49 %**  
Date 18/10/2023 07:47:55  
Executed by Carla AB

## Vehicle

Brand Tesla  
Model Model 3 - 77,8 kWh  
VIN 5YJ3E7EA2KF318568  
Mileage 71,477 km

## Analysis Result

# AVILOO SCORE

**89**  
/ 100

**High voltage battery usage and history**  
Analysis of charging & driving behavior

**62** / 70

**High voltage battery performance**  
Analysis of cell voltages and module temperatures.

**27** / 30

**High voltage battery control unit**  
Check of signals and calculations of the battery management control unit.




**Vehicle communication interface**  
Check of communication via the diagnostic interface.



  
DI Wolfgang Berger MBA  
Managing director

  
DI Nikolaus Mayerhofer  
Managing director

  
Dr. Marcus Berger  
COO/CFO and Partner



# EXPLANATION OF THE BATTERY FLASH TEST

## ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

## FLASH TEST EXECUTION PROTOCOL

07:47:55 Flash Test started.  
✓ Vehicle detected.  
✓ Starting data acquisition.  
✓ Finished data acquisition.  
✓ Analyzing data.  
✓ Analysis completed.

## DETAILED RESULTS OF PERFORMED CHECKS

### Vehicle Information

VIN	5YJ3E7EA2KF318568
Date	18/10/2023 07:47:55
Mileage	71,477 km

### Measurements High Voltage System

Battery temperature	20.5 °C
Maximum cell temperature deviation	1 °C
Pack voltage	363.59 V
Maximum cell voltage deviation	4 mV
Peak current during check	-4.5 A
State of Health (SoH - read from car manufacturer)*	91.11 %

\*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.

