



FLASH TEST REPORT

Execution

State of charge Date Executed by 67.34 % 09/08/2024 15:05:51 Carla AB

Brand Model VIN Mileage

Vehicle

Tesla Model X 5YJXCCE45KF161872 107,022 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	65 / 70
High voltage battery performance Analysis of cell voltages and module temperatures.	28 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	~
Vehicle communication interface Check of communication via the diagnostic interface.	v

Belec

Dr. Marcus Berger CEO and Partner





DI Nikolaus Mayerhofer

CTO and Founder

EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

- V FLASH Test started.
- ~ Starting data acquisition.
- 1 Vehicle detected.
- / Finished data acquisition.
- ~ Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN Date Mileage	5YJXCCE45KF161872 09/08/2024 15:05:51 107,022 km
Measurements High Voltage System	
Battery temperature	27.71 °C
Maximum cell temperature deviation	1.73 °C
Pack voltage	374.89 V
Maximum cell voltage deviation	14.44 mV

Peak current during check



AVILOO GmbH IZ NÖ-Süd, Straße 16, Objekt 69/5 Tel: +43 2236 374 036 2355 Wiener Neudorf

Web: www.aviloo.com FN: 502117 h

Mail: info@aviloo.com UID Nr.: ATU 737 81605



-4.11 A