



FLASH TEST REPORT

| F | ! |
|----------|------|
| Execut | INN |
| LAGGUL | 1011 |

State of charge Date Executed by 65.38 % 26/07/2023 08:05:25 Carla AB Brand Model VIN Mileage

Vehicle

Tesla Model S 5YJSA7E28JF253045 62,910 km

Analysis Result

AVILOO SCORE



| High voltage battery usage and history Analysis of charging & driving behavior | 45 / 50 |
|---|-----------------------------|
| High voltage battery performance Analysis of cell voltages and module temperatures. | 28 / 30 10 / 10 5 / 5 |
| High voltage battery control unit Check of signals and calculations of the battery management control unit. | |
| Electrical low voltage system Check of 12 V battery state and power supply. | |
| Vehicle communication interface | |

DI Wolfgang Berger MBA Managing director

Check of communication via the diagnostic interface.

DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

08:05:22 AVILOO Box connected.

08:05:25 Flash Test started.

08:09:38 Starting data acquisition.

08:09:38 Vehicle detected.

08:10:08 Finished data acquisition.

08:10:18 Analyzing data.08:10:20 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 5YJSA7E28JF253045

 Date
 26/07/2023 08:05:25

 Mileage
 62,910 km

Measurements High Voltage System

Battery temperature 29.45 °C
Maximum cell temperature deviation 0.92 °C
Pack voltage 326.69 V
Maximum cell voltage deviation 14.83 mV
Peak current during check -3.84 A

Measurements Low Voltage System

Power supply 12V system 13.35 V



Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

