



FLASH TEST REPORT

Execution

State of charge Date Executed by

43 % 02/02/2024 15:37:33

1 15:37:33 Model Carla AB VIN Mileage

Vehicle

Brand

Audi e-tron 55 - 95 kWh WAUZZZGE0NB002813 54,256 km

Analysis Result

AVILOO SCORE



65 / 70

26 / 30

High voltage battery usage and history Analysis of charging & driving behavior

High voltage battery performance

Analysis of cell voltages and module temperatures.

High voltage battery control unit Check of signals and calculations of the battery management control unit.

check of signals and calculations of the battery management control unit.

Vehicle communication interface

Check of communication via the diagnostic interface.

DI Wolfgang Berger MBA CSO and Founder

I Nikolaus Mayerhofer CTO and Founder



Dr. Marcus Berger

CEO and Partner



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

15:37:30 AVILOO Box connected.

- FLASH Test started.
- ✓ Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 WAUZZZGE0NB002813

 Date
 02/02/2024 15:37:33

 Mileage
 54,256 km

Measurements High Voltage System

Battery temperature 12 °C

Maximum cell temperature deviation 4 °C

Pack voltage 393.63 V

Maximum cell voltage deviation 7 mV

Peak current during check -5.59 A

State of Health (SoH - read from car manufacturer)* 85.33 %

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h

