



## **FLASH TEST REPORT**

21/08/2023 10:04:51

_ \/		-	<b>A B</b>
-x	3(:1		
Exe			$\mathbf{v}$

State of charge Date Executed by Vehicle

Brand Model VIN Mileage

13 %

Carla AB

Volkswagen ID3 - 58 kWh WVWZZZE1ZPP019605 7,280 km

### **Analysis Result**

# **AVILOO SCORE**

97/100

High voltage battery usage and history Analysis of charging & driving behavior	48 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	<b>29</b> / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	<b>5</b> / 5
Vehicle communication interface Check of communication via the diagnostic interface.	<b>5</b> / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director Dr. Marcus Berger COO/CFO and Partner





## EXPLANATION OF THE BATTERY FLASH TEST

#### **ANALYSIS METHOD**

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

#### FLASH TEST EXECUTION PROTOCOL

10:04:48 AVILOO Box connected.

10:04:51 Flash Test started.

10:04:54 Vehicle detected.

10:04:59 Starting data acquisition.

10:07:00 Finished data acquisition.

10:07:09 Analyzing data.

10:07:10 Analysis completed.

#### **DETAILED RESULTS OF PERFORMED CHECKS**

#### **Vehicle Information**

 VIN
 WVWZZZE1ZPP019605

 Date
 21/08/2023 10:04:51

 Mileage
 7,280 km

#### Measurements High Voltage System

Battery temperature	17.88 °C
Maximum cell temperature deviation	0.5 °C
Pack voltage	383.04 V
Maximum cell voltage deviation	9.04 mV
Peak current during check	-5.63 A
State of Health (SoH - read from car manufacturer)*	96.12 %

#### Measurements Low Voltage System

Power supply 12V system 14.58 V

\*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h

