



FLASH TEST REPORT

Execution

State of charge 33.8 % 04/07/2024 14:34:15 Date

Executed by

Model Carla AB VIN Mileage

Vehicle

Brand

DS Automobiles 3 Crossback E-Tense - 50 kWh VR1UJZKXZLW025276 44,725 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history

66 / 70 Analysis of charging & driving behavior

High voltage battery performance

Analysis of cell voltages and module temperatures.

High voltage battery control unit

Check of signals and calculations of the battery management control unit.

Vehicle communication interface

Check of communication via the diagnostic interface.

28 / 30

Dr. Marcus Berger CEO and Partner

DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

14:34:12 AVILOO Box connected.

- FLASH Test started.
- 1 Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN VR1UJZKXZLW025276 Date 04/07/2024 14:34:15 Mileage 44,725 km

Measurements High Voltage System

Battery temperature 20 °C Maximum cell temperature deviation 2°C 388.75 V Pack voltage Maximum cell voltage deviation 9.02 mV Peak current during check -2.61 A State of Health (SoH - read from car manufacturer)* 92.12 %





2355 Wiener Neudorf

Web: www.aviloo.com FN: 502117 h

Mail: info@aviloo.com UID Nr.: ATU 737 81605



^{*}The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.