



FLASH TEST REPORT

Execution

State of charge Date Executed by 41.13 % 20/12/2023 12:58:59 Carla AB

Vehicle

Brand Model VIN Mileage

Jaguar I-Pace - 90,2 kWh SADHA2B15M1608182 60,054 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	65 / 70
High voltage battery performance Analysis of cell voltages and module temperatures.	27 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	 ✓
Vehicle communication interface Check of communication via the diagnostic interface.	v

Dr. Marcus Berger CEO and Partner

DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

12:58:56	AVILOO Box connected	
----------	----------------------	--

- ✔ Flash Test started.
- Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

Measurements High Voltage System			
Mileage	60,054 km		
Date	20/12/2023 12:58:59		
VIN	SADHA2B15M1608182		

Battery temperature14 °CMaximum cell temperature deviation1 °CPack voltage392.18 VMaximum cell voltage deviation7 mVPeak current during check-12.65 AState of Health (SoH - read from car manufacturer)*91 %

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



AVILOO GmbH

Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

