



## FLASH TEST REPORT

**Execution** Vehicle

State of charge
Date 19/09/2024 13
Executed by Ca

40 % Brand 19/09/2024 13:47:33 Model Carla AB VIN Mileage Polestar 2 - 78 kWh LPSVSEDEEML005035 82,029 km

### **Analysis Result**

# **AVILOO SCORE**



**High voltage battery usage and history** Analysis of charging & driving behavior

**65** / 70

High voltage battery performance

**28** / 30

Analysis of cell voltages and module temperatures.

#### High voltage battery control unit

Check of signals and calculations of the battery management control unit.



#### Vehicle communication interface

Check of communication via the diagnostic interface.



Dr. Marcus Berger CEO and Partner DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





#### **EXPLANATION OF THE BATTERY FLASH TEST**

#### **ANALYSIS METHOD**

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

#### FLASH TEST EXECUTION PROTOCOL

13:47:30 AVILOO Box connected.

- FLASH Test started.
- Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

#### **DETAILED RESULTS OF PERFORMED CHECKS**

#### **Vehicle Information**

VIN LPSVSEDEEML005035 Date 19/09/2024 13:47:33 Mileage 82,029 km

#### Measurements High Voltage System

• • •	
Battery temperature	18.5 °C
Maximum cell temperature deviation	2.03 °C
Pack voltage	392.4 V
Maximum cell voltage deviation	7.92 mV
Peak current during check	-22.75 A
State of Health (SoH - read from car manufacturer)*	91.77 %

<sup>\*</sup>The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



Web: www.aviloo.com FN: 502117 h

Mail: info@aviloo.com UID Nr.: ATU 737 81605

