



FLASH TEST REPORT

19.5 %

Carla AB

Execution

State of charge Date

12/01/2024 09:30:48

Executed by

Vehicle

Brand Model VIN Mileage

Skoda Enyaq iV - 77 kWh TMBJC7NY1NF024881 46,397 km

Analysis Result

AVILOO SCORE

68 / 70

29 / 30

High voltage battery usage and history

Analysis of charging & driving behavior

High voltage battery performance

Analysis of cell voltages and module temperatures.

High voltage battery control unit

Check of signals and calculations of the battery management control unit.

Vehicle communication interface

Check of communication via the diagnostic interface.

Dr. Marcus Berger CEO and Partner

CSO and Founder

CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

09:30:45 AVILOO Box connected.

- Flash Test started.
- ✓ Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 TMBJC7NY1NF024881

 Date
 12/01/2024 09:30:48

 Mileage
 46,397 km

Measurements High Voltage System

Battery temperature 13.5 °C

Maximum cell temperature deviation 2.38 °C

Pack voltage 342.02 V

Maximum cell voltage deviation 4.89 mV

Peak current during check -9.26 A

State of Health (SoH - read from car manufacturer)*



Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h



^{*}The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.