THE TELECOMLINE SERIES

12-00642

Single pair Analogue Line protector

Features

- Economical single pair protection
- Low residual voltage
- Meets industry standards
- Reduces down time
- Increases network reliablility
- 2 year warranty




Application

The Kp1 Hybrid series single line protector uses state of the art semiconductor technology to protect telecom systems and networks from the damaging effects of induced lighting, AC induction and electrostatic discharges. In the normal mode of operation, the protection module is transparent to the functioning of the telecommunication system, but when the voltages exceed the breakdown voltages, the protection devices activate and divert the harmful energy away from the equipment being protected.


The single line protectors are designed to interface with Krone LSA Plus * disconnect blocks, and together with the earth bars, protect applications at telephone exchanges, remote cellular sites, building entrance terminations and equipment at customer premises.

Specifications	
Application	Voice / Data
Max operating voltage	230VDC
Max operating current	0.3A
Max discharge current 8/20 differential mode	5kA
Max discharge current 8/20 common mode	10kA
Residual voltage at 5kA differential mode	Approx. 200V
Residual voltage at 5kA common mode	Approx. 200V
Series resistance (per leg)	None
Data rate	1MHz
Temperature range	0°C to +70°C
Data speed	100KHz

Dimensions



Circuit diagram



*Krone and LSA plus are registered trademarks of Krone GMBH, Germany

Designed and Manufactured by:
Clearline Protection Systems (Pty) Ltd
Roan Crescent Corporate Park North, Old Pta Road, Midrand, South Africa
P.O. Box 5985, Halfway House, 1685
Tel: +27 (0) 11 848-1111
Fax: +27 (0) 11 314-3880
E-mail: sales@clearline.co.za
www.clearline.co.za

A member of Community Investment VENTURES

Clearline
The Electronic Protection Company