Crest Industrial Chemicals, Inc.●1737 County Road 57, Rosharon, Texas 77583 ● Phone (713) 780-1828 ● Toll Free Tel (800)622-9006 ● Fax (713) 583-9957

CRESTCHEMICALS

PAC-4

Multi-Purpose Heavy Duty Steam Cleaner

DESCRIPTION

Crest PAC-4 is a white, slightly yellowish powdered cleaner designed for steam cleaning, hot or cold high pressure cleaners, mopping floors, mechanical floor scrubbers, and general purpose cleaning of heavily soiled surfaces. Crest PAC-4 can be used on all ferrous metals when used at recommended dilutions, from cars to heavy construction equipment and concrete floors.

Powdered cleaner is easy to use--readily mixes with cold water.
Versatile - Can be mixed to meet different cleaning needs.
Built in water conditioner reduces scale build up.
Free rinsing-leaves no hard water deposits.
Free of heavy metals, chelates, and resin soaps.
Material is biodegradable.

MILITARY SPECIFICATIONS

Meets or exceeds all requirements for MIL-Spec A-A-59133 Type I, which supersedes P-C-437B Type I

METHOD OF USE

Light Duty	Use 1 ounce of PAC-4 per gallon of water to remove mud, road oils, and insects commonly found on cars and trucks. At this concentration no harm is usually done to nicely painted surfaces. Do not apply to painted surfaces if the concentration is higher.
Medium Duty	Use 2-4 ounces of PAC-4 per gallon of water to clean 5th wheels, running gear, engine blocks, and light duty floor cleaning. It will remove most heavy greases, oils, and asphalt at this concentration.
Heavy Duty	Use 6-16 ounces of PAC-4 per gallon of water to clean heavy construction equipment, railroad equipment, heavy floor cleaning in mechanical floor scrubbers, loose rust and loose paint. At this concentration it will remove light, flaky rust.
Rinse	Rinse well with cold or hot water.
Storage	Store in dry area with container cover tightly closed.

Crest PAC-4 will save time and money if used properly. It conditions hard water so no hard water scale will build in a steam cleaner. It has a material to lubricate equipment.

WARNING

Avoid contact with skin, eyes and clothing. Protective clothing such as face shields, rubber gloves, aprons and boots should be worn when handling this material. Refer to product label and material safety data sheet for additional precautionary and handling information.

PACKAGING

PAC-4 is packaged in 125 pound kegs and 450 pound drums.

Product should be stored at no lower than 50°F and no higher than 100°F.

WARRANTY AND LIABILITY DISCLAIMER

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience; however, since conditions of actual use are beyond our control, any recommendations, or suggestions, are made without warranty, expressed or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.

Rev. 061917