CRESTCHEMICALS

PPW-12 Blue
Liquid Heavy Duty Cleaner

Description

Crest PPW-12 Blue is a heavy-duty, nonflammable, general purpose liquid cleaner, specifically formulated for cleaning of all metal surfaces. PPW-12-Blue will remove dirt, oil films, grease, light carbon and exhaust stains from painted or unpainted surfaces. It is free rinsing to eliminate the danger of paint streaking sometimes encountered in other liquid cleaners. This product will not leave white deposits or streaks even if allowed to dry on the surface.

- The cleaner is translucent blue in color and is free from any sediment.
- The solvent odor not objectionable during use and leaves no residual odor.
- Under normal storage conditions (32° to 140°F) the cleaner will not change in color or physical state or suffer loss in cleaning effectiveness for a period of at least one year.

Specifications

This product meets or exceeds all qualifications for the following:

- Douglas (CDS No.1) Boeing (06-17487)
- Aerospace material specifications AMS 1526A
- MIL-PRF-87937D Type II, Type IV

Method of Use

Application Methods

- **Spray:** Apply with high pressure spray equipment, or with a barrel pump.
- **Immersion:** Apply with high pressure pot.

Mixing Instructions

- Maximum concentration for cleaning in extreme cases: 1 part PPW-12, 1 part water
- Medium Duty Cleaning : 1 part PPW-12, 5 parts water
- Normal cleaning: 1 part PPW-12, 10 parts water
- Light Cleaning: 1 part PPW-12, 20 parts water

Application Instructions

1. Apply with high pressure spray equipment, pressure pot or with a barrel pump.
2. Allow PPW-12 to sit for 5 to 10 minutes.
3. Agitate with suitable brush or mop and flush off with a large volume of water.

Caution

PPW-12 is non-corrosive to aluminum, magnesium, cadmium, anodized aluminum and ferrous alloys and will not cause hydrogen embrittlement of high strength steel. It will not attack asphalt and is non-crazing to Plexiglas. Refer to product labels and Safety Data Sheets for precautionary and handling information.

Product should be stored at no lower than 50°F and no higher than 100°F.

Warranty and Liability Disclaimer

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience; however, since conditions of actual use are beyond our control, any recommendations, or suggestions, are made without warranty, expressed or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.

1737 County Road 57, Rosharon, Texas 77583 • 713-780-1828 • crestchemicals.com