CRESTCHEMICALS

Stripper 29
Viscous, Non-Phenolic Lacquer Paint Stripper

Description
Crest Stripper 29 is a viscous, methanol-activated, non-phenolic paint remover that easily and quickly strips such coatings as baked enamels, zinc-chromated primers, synthetic enamels, acrylics, alkyds, varnish, and lacquers. This product is also used to remove writings on concrete and brick walls. This product will cling on all surfaces, vertical or horizontal.

To prevent evaporation, Stripper 29 contains a self-forming surface film that will decrease the rate of evaporation and extend the working life of the stripper. Stripper 29 is non-corrosive to aluminum, magnesium, anodized aluminum, ferrous alloys, concrete and brick.

Specification
This product meets or exceeds all qualifications for the following:
- TT-R-251J Type III Class B

Method of Use
Application Methods
- Spray
- Brush

Concentration
- Use as received.

Equipment
- Spray on with a non-atomizing sprayer. When brush applied, daub to give a thick coat. Do not brush on the stripper-like paint.

Stripping
- Allow sufficient dwell time for thorough loosening or blistering of the paint. When paint is loosened thoroughly, agitate all areas with a stiff brush. If paint is still adhering in some areas, reapply and allow additional time before rinsing with water.
  - Do ***not*** apply Stripper 29 to a wet surface, as this will cause the stripper not to work.

Rinsing
Stripper 29 and paint residues may be rinsed with a high pressure, high volume cold water or with a steam cleaning machine after most of the paint stripper has been removed from the surfaces. Water on lacquers will ball up and make a mess. Slight brushing during the rinse operation insures complete removal of all residues.

Caution
Stripper 29 will attack plastics; therefore, Plexiglas windows should be protected. Also, Stripper 29 will attack rubber window seals and tires. Store the stripper in an area out of direct sunlight. Also keep the stripper from freezing. Product should be stored at no lower than 50°F and no higher than 100°F. Refer to product labels and Safety Data Sheets for precautionary and handling information.

Warranty and Liability Disclaimer
The above information and recommendations concerning this product are based upon our laboratory tests and field use experience; however, since conditions of actual use are beyond our control, any recommendations, or suggestions, are made without warranty, expressed or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.

1737 County Road 57, Rosharon, Texas 77583 • 713-780-1828 • crestchemicals.com