### **Product Data Sheet**

# Glare's Intermediate - 03200

### Description

Glares Intermidate 03200 is based on non yellowing modified synthetic alkyd Resin. It offer good corrosion resistance and dries very fast, excellient finish and durability of film

#### **Product data**

**Product code** 

03200

**Gloss** Matt

Volume solids (%)

50±5

Specific gravity (kg/L)

 $1.2 \pm 0.1$ 

### **Application**

Mixing ratio		NA
Thinner		Glare's Thinner
Tillillei		03400
Pot life	(Hour)	NA

# **Drying and overcoating**

Touch dry	(Min.)	3-5.
Hard dry	(Hour)	1-2.
Overcoating	(Hour)	1-2.

#### **Film Thickness**

Dry film	(Micron)	25
Wet film	(Micron)	50
Theoretical spreading rate	(m²/L)	12- 14 (By Brush)

### Storage

Shelf life	(Months)	12

Shelf life from date of production, when stored in original, unopened containers.

Handling: Handle with care. Before and during use, observe safety labels on packaging and paint containers and follow all local and national safety regulations. Always consult Glare's Safety Data Sheet for this product along with the Product Data Sheet.

## For professional use only.

This Product Data Sheet ("PDS") relates to the supplied product ("Product") and is subject to updating from time-to-time. For updateed detail; please contact Glarecoat Private Limited.

## **GLARECOAT PRIVATE LIMITED**

www.glarecoat.com