Glare's Primer - 04100

Description

Glare's Primer 04100 is a two component of polyamide modified primer with low VOC and high performance coating mainly use for Industrial, architectural and marine maintaince. It has excellent chemical and abrasion resistance.

Product data

Product code
04100
Gloss
Matt
Volume solids (%)
55±5
Specific gravity (kg/L)
1.3 ± 0.1

Application

Drying and overcoating

Mixing ratio		0.167361111	Tou
Thinner		Glare's Thinner 04400	Har
Pot life	(Hour)	2-3 hrs.	Ove
Film Thickness			Sto
Dry film	(Micron)	30-35	She
Wet film	(Micron)	60-70	
Theoretical spreading rate	(m²/L)	12-14 (By Brush)	She in o

Touch dry	(Min.)	20-25.
Hard dry	(Hour)	4-6.
Overcoating	(Hour)	12.

Storage

Shelf life	(Months)	10

Shelf life from date of production, when stored in original, unopened containers.

Handling : Handle with care. Before and during use, observe safety labels on packaging and paint containers and follow all local and national safety regulations. Always consult Glare's Safety Data Sheet for this product along with the Product Data Sheet.

For professional use only.

This Product Data Sheet ("PDS") relates to the supplied product ("Product") and is subject to updating from time-to-time. For updateed detail ;please contact Glarecoat Private Limited.