

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TICKOPUR R 60

UFI:

KG10-S0GT-R00N-23NQ

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent. Intensive cleaner for the ultrasonic bath, concentrate.

Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik
Street: Heinrichstr. 3 – 4
Place: D-12207 Berlin, GERMANY
Telephone: +49 30 76880-280
E-mail: info@dr-stamm.de
Internet: www.dr-stamm.de
Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258

1.4. Emergency telephone

24-hours-emergency: Giftnotruf Berlin: +49 30 30686700 (german, english)

number:**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Skin Corr. 1; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

Sodium hydroxide; caustic soda

Signal word:

Danger

Pictograms:**Hazard statements**

H314

Causes severe skin burns and eye damage.

Precautionary statements

P280

Wear protective gloves/protective clothing and eye protection/face protection.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

The mixture does not contain substances $\geq 0.1\%$ of substances that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 2 of 10

3.2. Mixtures**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
7732-18-5	Water			80-90 %
	231-791-2			
1310-73-2	Sodium hydroxide; caustic soda			<12,5 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Skin Corr. 1A; H314			
527-07-1	Sodium gluconate			<5,0 %
	208-407-7		*1	
100085-64-1	Cocobetainamido Amphopropionate			<1,0 %
	309-206-8		*	
	Skin Irrit. 2; Eye Irrit. 2; Aquatic Acute 1; H315 H319 H400			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1310-73-2	215-185-5	Sodium hydroxide; caustic soda	<12,5 %
	oral: LD50 = 2000 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		
100085-64-1	309-206-8	Cocobetainamido Amphopropionate	<1,0 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % amphoteric surfactants.

Further Information

*Polymer

*1 Exempted from registration (Annex IV listed)

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.

After inhalation

In case of inhalation of aerosols/spray mist/splash spots: Consult physician. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do NOT induce vomiting. Consult physician.

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 3 of 10

4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx). Carbon dioxide (CO2).

5.3. Advice for firefighters

Special protective equipment for firefighters Use appropriate respiratory protection. In case of fire and/or explosion do not breathe fumes.

Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from unprotected people. Keep upwind. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up**Other information**

Clean contaminated articles and floor according to the environmental legislation. Treat the recovered material as prescribed in the section on waste disposal. Suitable material for taking up: Sand Universal binding agent. earth. Sawdust.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

It is recommended to design all work processes always so that the following is excluded: skin contact. Eye contact.

Advice on protection against fire and explosion

The product is not: Oxidizing. Flammable. Explosive.

Advice on general occupational hygieneDo not eat, drink, smoke or sneeze at the workplace.
Take off immediately all contaminated clothing.
Wash hands before breaks and after work.**7.2. Conditions for safe storage, including any incompatibilities**

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 4 of 10

Requirements for storage rooms and vessels

Store only in original container.

Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Cleaning agent.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1310-73-2	Sodium hydroxide; caustic soda			
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	local	1 mg/m ³

8.2. Exposure controls**Appropriate engineering controls**

Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Suitable material:

PE (polyethylene). Layer thickness: 0,5 mm penetration time (maximum wearing period): >=8h

CR (polychloroprenes, Chloroprene rubber). 0,5 mm penetration time (maximum wearing period): >=8h

NBR (Nitrile rubber). 0,35 mm penetration time (maximum wearing period): >=8h

Butyl rubber. FKM (Fluoroelastomer (Viton)). 0,5 mm penetration time (maximum wearing period): >=8h

Breakthrough times and swelling properties of the material must be taken into consideration.

Recommended protective gloves brand: Camapren 722, Manufacturer: KCL, Or comparable articles from other companies.

Skin protection

Lab apron.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	clear, light yellow
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point:

Test method
-15 °C

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 5 of 10

Boiling point or initial boiling point and boiling range:	100 °C
Flammability:	non-flammable
Lower explosion limits:	not applicable
Upper explosion limits:	not applicable
Flash point:	No flash point up to 100 °C.
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value (at 20 °C):	13,6 (conc.) 12,3 (1 %) DGF H-III 1
Viscosity / kinematic:	not determined
Water solubility: (at 20 °C)	complete miscible
Solubility in other solvents not determined	
Dissolution rate:	not determined
Partition coefficient n-octanol/water:	not determined
Dispersion stability:	not determined
Vapour pressure:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,160 g/cm ³ DIN 12791
Bulk density:	not applicable
Relative vapour density:	not determined
Particle characteristics:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not Explosive.

Sustaining combustion:

No data available

Oxidizing properties

not oxidizing.

Other safety characteristics

Evaporation rate:

not determined

Sublimation point:

not determined

Softening point:

not determined

Pour point:

not determined

Viscosity / dynamic:

not determined

Flow time:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Exothermic reactions with: acid, concentrated.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapors.

10.5. Incompatible materials

acid, concentrated. Reducing agents.

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 6 of 10

10.6. Hazardous decomposition products

None, in case of proper use.

Further information

Do not mix with other products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1310-73-2	Sodium hydroxide; caustic soda				
	oral	LD50 2000 mg/kg	rat		
100085-64-1	Cocobetainamido Amphopropionate				
	oral	LD50 >2000 mg/kg	Ratte	OECD 401	
	dermal	LD50 >2000 mg/kg	Ratte	OECD 402	

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage. (On basis of test data)

Serious eye damage/eye irritation: Causes serious eye damage. (On basis of test data)

Irritant effect on the skin: corrosive. Irritant effect on the eye: corrosive.

Sensitising effects

Based on available data, the classification criteria are not met.

not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Other information**

The mixture does not contain substances $\geq 0.1\%$ of substances that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 7 of 10

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge. due to the alkaline character of the product, usually, it has to be neutralized before contaminated effluents are introduced into the waste water treatment system.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1310-73-2	Sodium hydroxide; caustic soda					
	Acute fish toxicity	LC50	125 mg/l	96 h	Gambusia affinis	SDB Lieferant
	Acute crustacea toxicity	EC50	40,4 mg/l	48 h	Ceriodaphnia	ECHA
527-07-1	Sodium gluconate					
	Acute fish toxicity	LC50	>10000 mg/l	96 h		
100085-64-1	Cocobetainamido Amphopropionate					
	Acute fish toxicity	LC50	15 mg/l	96 h	Regenbogenforelle	OECD 203
	Acute algae toxicity	ErC50	0,15 mg/l	72 h	Selenastrum capricornutum	OECD 201
	Acute crustacea toxicity	EC50	4,4 mg/l	48 h	Daphnia magna	OECD 202
	Acute bacteria toxicity	EC50	>100 mg/l ()		Belebtschlamm	OECD 209

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
527-07-1	Sodium gluconate			
		98 %	2	
100085-64-1	Cocobetainamido Amphopropionate			
	OECD 301A	>70 %	28	
	easily biodegradable			

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
not applicable

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 8 of 10

Disposal recommendations

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

List of Wastes Code - residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

List of Wastes Code - used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packings can be re-cycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B
Segregation group:	18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 9 of 10

Hazard label: 8
Special Provisions: A3 A803
Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2
IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special precautionary measures are necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Hazchem code: 2R

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes: 0 % (0 g/l)**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Data changed from previous versions: 1.4., 2.3., 7.3., 9.1., 9.2., 11.2., 14.5, 14.6., 14.7.

Abbreviations and acronyms

Skin Corr: Skin corrosion

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

Aquatic Acute: Acute aquatic hazard

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data

Relevant H and EUH statements (number and full text)

H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

TICKOPUR R 60

Revision date: 12.11.2025

No.: 83028

Page 10 of 10

H400 Very toxic to aquatic life.

Further Information

Training instructions: Follow the instructions for use on the label.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	TICKOPUR R 60	IS, PW	0	35	8a, 9, 13	8a	0	26	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)