

TECHNICAL DATA SHEET

PRODUCT NAME		E-GLASS FIBER CHOPPED STRAND MAT (POWDER) 300G/M2-1040MM
TEST ITEM		STANDARD VALUE
UNIT MASS G/M2		300±7%
R20(%)		≤0.80
MOISTURE(%)		≤0.20
LOSS OF IGNITION(%)		2.5-4.0
TENSILE BREAKING FORCE(N/150MM*200MM)	WARP	≥100
	WEFT	≥100
RESIN WET-OUT RATES		≤50
STANDARD		GB/T 17470-2007



TECHNICAL DATA SHEET

PRODUCT NAME		E-GLASS FIBER CHOPPED STRAND MAT (POWDER) 450G/M2-1040MM
TEST ITEM		STANDARD VALUE
UNIT MASS G/M2		450±7%
R20(%)		≤0.80
MOISTURE(%)		≤0.20
LOSS OF IGNITION(%)		2.5-4.0
TENSILE BREAKING FORCE(N/150MM*200MM)	WARP	≥100
	WEFT	≥100
RESIN WET-OUT RATES		≤50
STANDARD		GB/T 17470-2007

TECHNICAL DATA SHEET

PRODUCT NAME		E-GLASS FIBER CHOPPED STRAND MAT (POWDER) 600G/M2-1040MM
TEST ITEM		STANDARD VALUE
UNIT MASS G/M2		600±7%
R20(%)		≤0.80
MOISTURE(%)		≤0.20
LOSS OF IGNITION(%)		2.5-4.0
TENSILE BREAKING FORCE(N/150MM*200MM)	WARP	≥100
	WEFT	≥100
RESIN WET-OUT RATES		≤50
STANDARD		GB/T 17470-2007