

# Technical Data Sheet

**Supplier:** Changzhou Pro-Tech Trade Co.,Ltd.

**Goods:** Chopped Strand Mat(Powder Binder)

## Properties:

Easy air removal and rapid resin impregnation  
Drapes well to suit the surface of intricate moulds  
Fast wet-through and wet-out  
Easy handing and better appearance of the composite parts  
Good surface bonding and high strand integrity. Compatible with  
Unsaturated polyester resins.

## Product Characteristics:

Test Item	Standard Value		Standard No.
	450Gr/m2	300Gr/m2	
Mass Per Unit Area(g/m2)	414-472	276-315	ISO3374-2000
Width(mm)	1040±5	1040±5	ISO5025-1997
Loss on ignition (%)	1.8-8.5	1.8-8.5	ISO1887-1995
Moisture content(%)	0.2MAX	0.2MAX	ISO3344-1997
Breaking Force (N)	60MIN	60MIN	ISO3342-1995

## Packaging:

Packaging:

Each roll is wound onto paper core and packed in plastic bag plus individual cardboard box, or, as per customer's request. All of goods packed with pallet.

## Storage:

Glass fiber products should be preferably be stored at room temperature and a relative humidity between 50% and 70%

常州普泰貿易有限公司  
CHANGZHOU PRO-TECH TRADE CO., LTD  
  
Authorized Signature