

PRODUCT DESCRIPTION

Petrocar Dexron VI Trans+ is a full synthetic fluid specially developed for all types of automatic transmission (manual or sequential, electronic control, etc.) with or without clutches requiring a DEXRON VI fluid.

APPLICATION

Petrocar Dexron VI Trans+ is recommended for the most recent convertible automatic gearboxes, torque converters, power steering and hydraulic or mechanical systems for which DEXRON III H or DEXRON II D fluids are required in addition to all types of automatic transmissions requiring DEXRON VI fluid.

Petrocar Dexron VI Trans+ main advantages are:

- Allows lower fuel consumption on cars equipped with automatic gearboxes.
- Reduces fuel consumption friction.
- Prevents vibrations of the engine flywheel.
- Protects the ever-larger, compact and loaded gears.
- Ensures greater responsiveness of gear changes making them softer and faster.
- Improves the operation of automatic cold change.
- Guarantees longevity, better oxidation resistance and higher stability at high temperatures.
- Anti-wear, anti-corrosion and anti-foam protection.

PERFORMANCE LEVELS AND APPROVALS

GM DEXRON VI

GM DEXRON III

GM DEXRON III-H

Ford MERCON LV

M315 TYPE 1A

SUZUKI ATF 3309 – 3314 - 3317

RENAULT NISSAN MATIC C/D/J/K/S

TYPICAL CHARACTERISTICS

Petrocar Dexron VI Trans+	Testing procedure	Typical Values
Color	Visual	Red
Density@15°C, kg/m ³	ASTM D 1298	≥0.850
Viscosity @40°C, cSt	ASTM D 445	29 - 30.5
Viscosity @100°C, cSt	ASTM D 445	5.4 - 6
Viscosity Index	ASTM D 2270	≥150
Pour Point, °C	ASTM D 97	≤-45
Flash Point, °C	ASTM D 92	≥220