



# FLEET+ SAE 15W40

## PRODUCT DESCRIPTION

Petrocar Fleet+ SAE 15W40 is a last generation SHPDO (Super High Performance Diesel Oil) multigrade diesel engine oil blended with carefully selected base oils and additives and formulated to guarantee outstanding performances in the modern naturally aspirated and turbocharged diesel truck engines even working in harsh conditions.

Petrocar Fleet+ SAE 15W40 is fully compatible with all antipollution devices and exceeds the main OEM performances requirements.

## APPLICATIONS

Petrocar Fleet+ SAE 15W40 is recommended for all new vehicle engines and commercial vehicles where they are prescribed by the lubricant manufacturers with the technical specifications listed below.

## PERFORMANCE LEVELS AND APPROVALS

API CI-4/SL  
ACEA E7 – A3/B4  
VOLVO VDS-3  
MB 228.3  
MAN M3275  
MTU TYPE 2  
MACK EO-N /EO-M Plus  
RENAULT TRUCKS RLD/RLD-2  
CUMMINS CES 20076/77  
CAT ECF-2/ ECF-1-a  
DEUTZ DQC III-18  
ZF TE ML 04C/07C

## TYPICAL CHARACTERISTICS

<b>Petrocar Fleet+ SAE 15W40</b>	<b>Testing procedure</b>	<b>Typical Values</b>
Grade	-	15W40
Density @15°C, kg/m <sup>3</sup>	ASTM D 1298	≥ 865,0
Viscosity @100°C, cSt	ASTM D 445	12,5 – 16,3
Viscosity Index	ASTM D 2270	≥ 140
Pour Point, °C	ASTM D 97	≤ -27
Flash Point, °C	ASTM D 92	≥ 220
TBN - mg KOH/g	ASTM D 2896	≥ 9