



HYPER+ SAE 10W40

PRODUCT DESCRIPTION

Petrocar Hyper+ SAE 10W40 is a premium quality multigrade synthetic lubricant blended with isomerised base oil through a severe hydrogenation process and selected additives, designed to achieve the highest performance standards in gasoline and diesel engines.

Petrocar Hyper+ SAE 10W40 offers the following main advantages:

- Good low temperature properties to allow rapid lubrication after cold starting.
- Outstanding protection against wear to maximise engine life.
- Excellent detergent/dispersant properties for best soot control.
- Excellent thermal and oxidation stability increasing fuel economy and extended service intervals.

APPLICATIONS

Petrocar Hyper+ SAE 10W40 is intended for use in typical gasoline and diesel engine services, including turbo-charged engines in passenger cars, SUVs, light vans and light trucks and suitable for extended drain intervals as specified by engine manufacturers.

PERFORMANCE LEVELS AND APPROVALS

API SN

MB 229.31/229.51

VW 505.00/505.01

TYPICAL CHARACTERISTICS

Petrocar Hyper+ SAE 10W40	Testing procedure	Typical Values
Grade	-	10W40
Density @15°C kg/ m ³	ASTM D 1298	860
Viscosity @100°C,cSt	ASTM D 445	14,0
Viscosity Index	ASTM D 2270	130
Pour Point, °C	ASTM D 97	-30
Flash Point, °C	ASTM D 92	220