



RACING+ 4T – SAE 10W40

PRODUCT DESCRIPTION

Petrocar Racing+ 4T SAE 10W40 is a lubricant formulated with carefully selected base oils and synthetic components for 4-stroke engines and motorcycle clutch units of any brand and capacity, air or water cooled. Ideal when touring use is not severe.

Petrocar Racing+ 4T SAE 10W40 guarantees the following features:

- Excellent anti-wear capacity.
- Extraordinary oxidation resistance and thermal stability.
- High detergency / dispersion capacity with resistance to the formation of deposits.

Petrocar Racing+ 4T SAE 10W40 has a carefully balanced additive package that offers the following advantages:

- Ensuring maximum protection against friction.
- Drastically reducing the wear of mechanical parts.
- Facilitating the insertion of the driving gears, reducing oil consumption.

APPLICATIONS

Petrocar Racing+ 4T SAE 10W40 provides maximum protection for medium and high cylinder capacity engines with one, two, three or four cylinders, and ensures the care of all its components even under severe conditions of use and high speeds.

PERFORMANCE LEVELS AND APPROVALS

API SJ/SL

JASO MA

TYPICAL CHARACTERISTICS

Petrocar Racing+ 4T SAE 10W40	Testing procedure	Typical Values
Grade	-	10W40
Density, kg/m ³	ASTM D 1298	≥ 850
Viscosity, cSt a 40°C	ASTM D 445	≥78,0
Viscosity, cSt a 100°C	ASTM D 445	12,5 ÷16,3
Viscosity Index	ASTM D 2270	≥160
Pour Point, °C	ASTM D 97	≤-27
Flash Point, °C	ASTM D 92	≥ 210