



# RACING + 4T – SAE 20W50

## PRODUCT DESCRIPTION

Petrocar Racing+ 4T-SAE 20W50 is a mineral lubricant formulated with carefully selected base oils and specific additives that make it particularly recommended for all modern 4-stroke engines.

Petrocar Racing+ 4T-SAE 20W50 guarantees the perfect functioning of the clutch disks, avoiding skidding and premature wear in the joint lubrication systems of the engine and transmission.

Petrocar Racing+ 4T-SAE 20W50 shows the following properties:

- Good thermal stability.
- Excellent anti-wear capacity.
- Excellent oxidation resistance.
- Maximum protection against friction.
- High detergency and dispersion capacity.

## APPLICATIONS

Petrocar Racing+ 4T-SAE 20W50 is recommended for all for all modern 4-stroke engines, provides maximum protection and ensures the care of all its components even under severe conditions of use and high speeds.

## PERFORMANCE LEVELS AND APPROVALS

API SM

JASO MA

## TYPICAL CHARACTERISTICS

<b>Petrocar Racing+ 4T-SAE 20W50</b>	<b>Testing procedure</b>	<b>Typical Values</b>
Grade		20W-50
Density, kg/m <sup>3</sup>	ASTM D 1298	≥ 855
Kinematic Viscosity, cSt a 100°C	ASTM D 445	16.3 – 21.9
Viscosity Index	ASTM D 2270	≥145
Pour Point, °C	ASTM D 97	≤-24
Flash Point, °C	ASTM D 92	≥ 220