



**SILVER +
SAE 5W40**

PRODUCT DESCRIPTION

Petrocar Silver+ SAE 5W40 is a full synthetic lubricant blended with high quality synthetic base oils and selected additives.

Petrocar Silver+ SAE 5W40 is formulated to guarantee outstanding performances in the modern naturally aspirated and turbocharged gasoline and diesel engines even in harsh work conditions.

Petrocar Silver+ SAE 5W40 shows the following properties:

- High oxidation resistance.
- Excellent anti-wear protection.
- Excellent low temperature fluidity.
- Protection against the formation of sludge.

APPLICATIONS

Petrocar Silver+ 5W40 is recommended for all new generation cars, sport utility vehicles and light truck engines. Fully compatible with all anti-pollution devices and exceeds the main OEM performance requirements.

PERFORMANCE LEVELS AND APPROVALS

API SN

ACEA C3

MB 229.51

BMW LL04

VW 502.00/505.00/505.01

TYPICAL CHARACTERISTICS

Petrocar Silver+ 5W40	Testing procedure	Typical Values
Grade	-	5W-40
Density @15°C, kg/m ³	ASTM D 1298	850
Kinematic Viscosity @100°C, cSt	ASTM D 445	14,5
Viscosity Index	ASTM D 2270	170
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	210
Sulfated ash, %	ASTM D874	≤0,8
TBN, mg KOH/g	ASTM D2896	≥6