



SUPER+
SAE 20W50

PRODUCT DESCRIPTION

Petrocar Super+ SAE 20W50 is a premium quality multi-grade lubricant based on highly refined mineral oils and selected additives.

Petrocar Super+ SAE 20W50 gives outstanding performances in naturally aspirated or turbocharged engines, fueled by gasoline or diesel.

Petrocar Super+ shows following main benefits:

- High oxidation and thermal resistance.
- Enhanced engine protection against wear.
- Outstanding detergency/dispersion properties.

APPLICATIONS

Petrocar Super+ SAE 20W50 is suitable for engines with catalytic converters. It is recommended for gasoline and diesel engines that require API SL quality level of oil and greater protection at high temperatures. It is suitable for extended drain intervals where specified by the engine manufacturer.

PERFORMANCE LEVELS AND APPROVALS

API SL/CF/CF-4

ACEA A3/B4; E2

MB 227.0/228.1

VOLVO VDS-VDS 2

MTU TYPE 2

TYPICAL CHARACTERISTICS

Petrocar Super+ SAE 20W50	Testing Procedure	Typical Values
Grade	-	20W50
Density @ 15°C, Kg/m ³	ASTM D 1298	≥ 870
Viscosity @ 100°C, cSt	ASTM D 445	18,2
Viscosity Index	ASTM D 2270	≥ 145
Pour Point, °C	ASTM D 97	≤ -21
Flash Point, °C	ASTM D 92	≥ 220