

TECHNICAL DATA SHEET

ADAPTOR (A178)



PRODUCT CHARACTERISTICS		
Physical and Chemical properties		
STEEL GRADE	Conform to CAN/CSA G40.21-350W and/or ASTM A500 grade C standards or approved equivalent	
HOT DIP GALVANIZATION	Conform to ASTM-A123M	
Models	Standard characteristics	
A178 ADAPTOR	Round plate 2"Ø x 3/16" thick, with a 1 1/2"Ø x 2 3/4" lg. round tube	
Mechanical resistance		
EFFORTS	ULS ⁽¹⁾	SLS ⁽¹⁾
Compression in kN (lbs) ⁽²⁾	90 (20 250)	60 (13 500)

(1): ULS = Ultimate Limit State; SLS = Service Limit State

(2): The strengths shown in the table above represent the maximum capacities of the metal assembly of the part when connected to a pile with a diameter of 47 mm (1 7/8")

RECOMMENDED USE

A178 adaptors connect the adjustable head to the piles.

They are designed to support compressive loads only. The adaptors are simply deposited on the pile which does not allow any resistance to tension efforts.

In cases where piles are subjected to tensile or lateral loads, the use of another more appropriate adaptor will be required.

ADVANTAGES

- Product and installation are supplied;
- Can be installed in all climates, weather or ground conditions;
- Allows the adjustment of pile heads;
- The most reliable & economical solution available;
- Reusable and recyclable, environmentally friendly;
- Can be installed under an existing structure;
- No waiting time, you can build as soon as the installation is completed.

CCMC
13102-R



NORMATIVE INFORMATION

Postech screw pile accessories have been calculated and tested on-site by an engineering firm recognized by the CCMC. The purpose of these tests was to validate the mechanical resistance of Postech accessories.

MANUFACTURER:
Pieux Vistech - Postech Screw Piles
10260 Bourque boulevard,
Sherbrooke QC J1N 0G2
Tel. : 819.843.3003
Toll free: 1.866.277.4389
Fax. : 819.868.0793

postechpiles.com

Rev. 2022-02