



### NORMATIVE INFORMATION

This Postech pile has been the subject of calculations and/or physical tests. The aim of this work is to validate the mechanical resistance of the part. In accordance with CCMC technical guide TG-316216.01-15, referring to the National Building Code (NBC), and in compliance with the ISO-9001 quality management system.

**MANUFACTURER:**  
Pieux Vistech - Postech Screw Piles  
10260, Bourque boulevard  
Sherbrooke QC J1N 0G2  
Tel.: 819.843.3003  
Toll free: 1.866.277.4389  
Fax.: 819.868.0793  
[postechpiles.com](http://postechpiles.com)

### PRODUCT SPECIFICATIONS

#### Physical and Chemical Properties

<b>STEEL GRADE</b>	Conform to CAN/CSA G40.21-350W and/or ASTM A500 class C
<b>WELDING</b>	Conform to CSA W59
<b>HOT DIP GALVANIZATION</b>	Conform to ASTM-A123M
<b>THERMAL INSULATION</b>	Polyurethane foam injected inside the pile shaft

#### Standard Dimensional Specifications

<b>PILE SHAFT</b>	HSS 2 7/8" O.D. x 0.250" wall tk. round shaft (73 mm O.D. x 6.4 mm tk.)
<b>STANDARD LENGTHS</b>	Available in standard lengths of 7' & 10'
<b>HELIX DIAMETERS</b>	Standard diameters of 10", 12", 14" & 16" (254 mm to 406 mm)
<b>HELIX THICKNESSES</b>	5/16" (8 mm) for diameters of 10" 3/8" (9.5 mm) for diameters of 12" to 14" 1/2" (12.7 mm) for diameters of 16"
<b>BOLT CONNECTION HOLES</b>	2x through bolt holes for 3/4" (19 mm) diam. bolts & with a spacing of 3" (76 mm)

#### Structural Capacities

#### ULS <sup>(1)</sup>

#### SLS <sup>(1)</sup>

<b>MAX. COMPRESSION CAPACITY <sup>(2)</sup></b>	300 kN (67400 lb)	220 kN (49400 lb)
<b>MAX. TENSION CAPACITY <sup>(2)</sup></b>	185 kN (41500 lb)	135 kN (30300 lb)
<b>BENDING CAPACITY</b>	8 kN.m (5900 lb.ft)	5,9 kN.m (4300 lb.ft)
<b>MAXIMUM INSTALLATION TORQUE</b>	11520 N.m (8500 lb.ft)	-

#### COMPRESSIVE TORQUE CORRELATION FACTOR (K<sub>t</sub>)

8 ft-1 (26.25 m-1)

(1): ULS = Ultimate Limit State; SLS = Service Limit State.

(2): The specified capacities are only applicable to the steel assembly where the pile shaft is laterally supported. In all cases, the mechanical capacity of the extension must be validated by a licensed engineer, and with considerations for column buckling if installed in liquifying soils, peats or bogs

### DESIGN INFORMATION

In all cases, applicable loads must be validated by a professional licensed to practice under the appropriate provincial or territorial legislation.

#### BEARING CAPACITY

Postech products are designed to bear compressive, tension and lateral loads. The design of the shaft and the size of the blade depend on the load and on the bearing capacity of the soil. The monitoring of the applied torque on site allows for the confirmation of the allowable bearing capacity (SLS) of the soil. All capacities listed on this data sheet must be applied at the pile head less than 0.3 m (1 ft) above ground.

#### THERMAL INSULATION

Postech products are insulated by a process of injecting polyurethane foam in the piles shaft. The insulation system ensures that the inside of the pile is maintained at a temperature that will prevent ice or frost build-up at the base of the pile; providing optimal protection against frost heave.

### ADVANTAGES

- Product and installation are supplied.
- Can be installed in all climates, weather or ground conditions.
- Allows the adjustment of pile heads.
- The most reliable & economical solution available.
- Reusable and recyclable, environmentally friendly.
- Can be installed under an existing structure.
- No waiting time, you can build as soon as the installation is completed.

