



Portable Air Cooled Air Conditioners

Classic Plus 14

Cooling Capacity	Btu/hr. @ 95° At 60% Relative Humidity	13,200
Dimensions	Width (Inches) Depth (Inches) Height (Inches) Weight (Pounds) Shipping Weight	19 26 41 166 197
Electrical Characteristics	Power Supply (Volts) Power Consumption (Kilowatts) Current Consumption (Amperes) Fuse Size (Amperes) NEMA Plug Configuration Min-max Voltage Power Cord Gauge Power Cord Length (Feet)	115 1phase 1.3 11.9 15 5-15 105-125 Volt 14AWG (3 Core) 10
Compressor Characteristics	Compressor Type Refrigerant Operating Conditions: Min-max °F	Hermetic Rotary R-410A 70°-113°F, 50% RH
Fan Characteristics	<i>Evaporator:</i> Fan Type Air Flow (CFM) High/Low Max. External Static Pressure (Inches Of Water Gauge) <i>Condenser:</i> Fan Type Air Flow (CFM) High/Low Max. External Static Pressure (Inches Of Water Gauge)	Centrifugal 440/380 0.31 Centrifugal 880/760 0.19
Safety Devices	Compressor Overload Relay Fan Motor Protection Anti-freeze Thermostat Automatic Tank Shut-off Condensate Tank Capacity (Gallons) High-pressure Switch Compressor Short-cycle Protection Fan Mode Switch Automatic Restart Thermostat Control Panel	Yes Yes Yes Yes 5 N/A Yes Yes Yes Yes Programmable
Miscellaneous Features	Operating Cost Humidity Removed @ 60% RH Accommodates Condensate Pump Sound Level (Db) High/Low Max Evaporator Ducting Length*(Ft.) Max Condenser Ducting Length*(Ft.) <i>*subtract 10 Ft. For Every 90° Bend</i>	\$0.093 0.67 Yes 57/55 30 60



Portable Air Cooled Air Conditioners

Classic Plus 14

Power Supply 115 volts 60 hertz 1 phase 11.9 amperes

Width 19 inches

Depth 26 inches

Height 41 inches

Weight (net/shipping) lbs 166/197

All models are backed by a 12-month warranty with 36 months for the compressor.
All coils are treated with an acrylic resin coating for extended life and corrosion resistance.

